



# Tarasola®

## Essential Product card 2024





## SPECIFICATION

- The structure is made of extruded powder-coated aluminum.
- Electric motor control included in the price.
- Water drainage system included in the price.
- Possibility of powder coating in any RAL colour.
- Louvres rotate from 0° to 135°.
- Option of additional accessories:
  - lighting – LED Spot, LED Strip, LED Box i LED Line,
  - glazing
  - Screen ZIP,
  - shutters,
  - fixed wall panel,
  - infrared heaters,
  - wind, rain and temperature sensors.



Infrared heaters



Spot



Box



Line



Strip



Glazing



Shutters



Screen ZIP



Fixed wall panel



## COLOURS

### CONSTRUCTION



9010ST  
Colour cream-white  
similar to RAL9010  
\* Lead time as for  
a non-standard color



7016ST  
Colour  
anthracite-metallic  
similar to RAL7016

### ADDITIONAL COLOURS



Any colour from the  
RAL palette



Wood effect varnish



TIGER 3D Metallics,  
Series 68

### LOUVRES



9010ST  
Colour cream-white  
similar to RAL9010



7016ST  
Colour  
anthracite-metallic  
similar to RAL7016

### ADDITIONAL COLOURS



Any colour from the  
RAL palette




Wood effect varnish




TIGER 3D Metallics,  
Series 68


## PROJECTION (cm)




## CROSS-SECTION



## CROSS-SECTION OF SUPPORTING PILLAR (mm)




## WIDTH (cm)




## LOUVRES CROSS-SECTION


NEW




## LOUVRES ROTATION - LOUVRES PARALLEL TO THE WALL




## LOUVRES ROTATION - LOUVRES PERPENDICULAR TO THE WALL




## WATER DRAINAGE



## INTERNAL FIXING PLATE - STANDARD




## EXTERNAL FIXING PLATE - OPTION




UNPAINTED  
STAINLESS STEEL


## CONSTRUCTION DIMENSIONS USING EXTERNAL FIXING PLATES



## ESSENTIAL PAVILLON / TENDE



## ESSENTIAL GARDENA LOUVRES PERPENDICULAR



## ESSENTIAL GARDENA






TABLE FOR THE SNOW LOAD WITHOUT WIND PRESSURE FOR A STRUCTURE STANDING ON 4 PILLARS (kg/m<sup>2</sup>)

projection (cm)	number of louvres	width (cm)						
		220	270	295	330	365	400	450
200	9	620	490	350	290	180	150	120
300	14	590	450	310	190	160	150	120
400	19	450	430	290	180	170	140	120
500	24	420	340	250	165	160	120	120
600	29	240	220	165	130	130	120	120
700	34	220	160	140	120	120	120	120


# FIXED WALL PANEL




FRONT VIEW (CM)



VERTICAL CROSS-SECTION (MM)



HORIZONTAL CROSS-SECTION (MM)



## COLOURS

### STANDARD COLOURS - STRUCTURE/PANEL



9010ST  
Colour cream-white  
similar to RAL9010

\* Lead time as for  
a non-standard color



9007ST  
Colour grey  
aluminium similar  
to RAL9007



7016ST  
Colour anthracite-  
metallic similar  
to RAL7016 (in set)



9005ST  
Structural black  
colour similar to  
RAL9005

\* Lead time as for  
a non-standard color

### ADDITIONAL COLOURS



Any colour from  
the RAL palette



Wood effect  
varnish



TIGER 3D Metallics,  
Series 68

### STANDARD COLOURS - PANEL



9010ST  
Colour cream-white  
similar to RAL9010  
(in set)

\* Lead time as for  
a non-standard color



9007ST  
Colour grey  
aluminium similar  
to RAL9007



7016ST  
Colour anthracite-  
metallic similar  
to RAL7016



9005ST  
Structural black  
colour similar to  
RAL9005

\* Lead time as for  
a non-standard color

### ADDITIONAL COLOURS



Any colour from  
the RAL palette



Wood effect  
varnish



TIGER 3D Metallics,  
Series 68

## Colour

9010ST White structured  
(Lead time as for a non-standard color)

7016ST Anthracite structured

Any RAL colour

Wood effect varnish

TIGER 3D Metallics, Series 68

## Controls

### Motor

24 V DC Wired motor with power supply 150 W

### Controls TELECO

24V DC radio control unit for 1 motor

Optional sensors:

\* wind

\* rain

\* temperature

\* combination of temperature & rain sensors to detect snow

### Controls Somfy.

Somfy IO louver - 24V control unit for 1-2 motors

### Remote control TELECO

42 channel remote control, white / black

63 channel remote control, white / black

### Remote controls Somfy. IO

SITUO 1 IO remote control, single-channel

SITUO 5 IO remote control, five-channel

SITUO1 VARIATION IO remote control, single-channel (necessary to control RGB tape)

SITUO 5 VARIATION IO remote control, five-channel (necessary to control RGB tape)

NINA IO remote control, for 50 devices (necessary to control RGB tape)

NINA TIMER IO remote control, for 50 devices (necessary to control RGB tape)

### Weather sensors TELECO

Wind TELECO

Rain TELECO

Temperature TELECO


Rain and temperature sensors to detect snow  
TELECO

### Weather sensors Somfy. IO

Wind Eolis IO

Rain Ondeis 24V

## Lighting



Spot


### LED Spot

Controler white TELECO up to 25 spotlights

Additional control up to 25 spotlights Somfy IO

Additional control up to 50 spotlights Somfy IO

Min. 8 LED spotlights on whole construction,  
min. 3 LED spotlights on a louvres.



Strip

### LED Strip 8W - White

LED Strip RGB 8W

Controler white/RGB TELECO up to 28 lm (max. 4 pc LED strip)

Controler white SOMFY IO up to 18 lm (max. 4 pc LED strip)

Controler RGB SOMFY IO up to 18 lm (max. 4 pc LED strip)

Power supply up to 18 lm

Power supply up to 18-36 lm



Box

### LED Box

Controler white TELECO up to 25 spotlights

Additional control up to 25 spotlights Somfy IO

Additional control up to 50 spotlights Somfy IO

Min. 4 LED tubes in the structure,  
min. 2 tubes in the louvres.



Line

### LED Line

Controler white TELECO up to 25 spotlights

Additional control up to 25 spotlights Somfy IO

Additional control up to 50 spotlights Somfy IO

Min. 4 LED tubes in the structure.

## Smartphone control

TAHOMA SOMFY SWITCH

DAISY TELECO

## Infrared heaters

power

Infrared heater GR1 - controlled by a switch with a LOW GLARE emitter that generates less light, water-tight class IP65, colour: white or black, usually controlled by a wall switch. For external use.

1,5 kW

Infrared heater GR2 IR - a infrared heater with a built-in infrared receiver, remote control and a LOW GLARE emitter that releases less light. Water-tight class IP65, colour white or black, controlled by an infrared remote control (in set). For external use.

1,5 kW

Infrared heater GR3 Glass - the front of the radiator is a glass panel in black, with a LOW GLARE emitting less light, water tightness class Ip65, casing colour black, controlled as standard via a wall switch or an external control unit. For external use.

2 kW

Additional infrared remote control.


## Radio receivers for infrared heaters GR1, GR3

Control Unit for 1-2 infrared heaters 3 kW

GR, GR3 infrared heaters can be operated by TELECO 42-channel remote control on/off. No heat adjustment.



# Tarasola®



**Contact:**



+48 607 189 400

+48 502 342 842



export@tarasola.com

**Tarasola.com**

